

REMARKS:

The present amendment is submitted in an earnest effort to advance this case to issue without delay.

1. The priority claims acknowledgement in paragraph 13 of PTO 326 is appreciated.

2. A Substitute Specification is supplied herewith and contains section headings as well as the requested cross reference to related applications. A marked-up version of the Substitute Specification is also enclosed. The Substitute Specification does not contain any new matter.

3. A new claim 19 has been added to correspond to allowable claim 8 written in independent form.

4. Claims 1-10 have been replaced by new claims 11-18, carefully drafted to define the invention with particularity over the references of record and particularly the PHILLIPS reference as combined with NOVOPLAST.

The new claims call for a fencing system with a plurality of pales (20) and a rail (10) with fasteners (28) securing pales to the rail. Each of the pales (20) is generally tubular with a first wall (23) which is concave toward the rail (10) and a second wall (22) which is convex away from the rail. The walls of each pale

define a space between them, i.e. the pale is hollow. At least one fastener extends into a first wall (23) of each pale.

The fasteners draw the first wall of each pale against the rail with at least partial flattening of the first wall and the second walls are free from engagement by the fasteners.

The PHILLIPS reference, as can readily be seen, have the front and rear surfaces traversed by the bolt and, therefore, do not have second walls free from engagement by the fasteners. Nor can it be said that a first wall is drawn against the rail resiliently or otherwise.

In the NOVOPLAST patent also there are no two walls in the sense of the claimed pale.

Thus even if it would have been obvious to combine NOVOPLAST with PHILLIPS and to utilize FIG. 2 for that purpose, the combination would not meet the claimed structure.

Nevertheless it can scarcely be said that the tubular structure of NOVOPLAST is sufficiently similar to the pale (20) of the claimed system as to enable any teaching of the NOVOPLAST reference to be used in combination with PHILLIPS.

More specifically, "the citation, US 327,717 (PHILLIPS) shows solid concavo-convex fence posts having hooked bolts that hold together and but half lap joints of the horizontal bars.

By providing a hollow pale with a concave exterior surface facing the rail, the present invention gives a pale that is securely attached to the rail without exposing the fixing means.

In PHILLIPS, the bolt is completely exposed and a trivial matter for someone approaching the face of PHILLIPS's fence post to dismantle it. Further, it is not clearly evident that the PHILLIPS's fence post is flattened during its fixing or is stressed; it could be sufficiently thick and rigid that no significant flattening or stressing occurs.

There is no suggestion to provide PHILLIPS in a hollow form, but retain the concavo-convex shape, and to cause the fixing means to engage the exterior concave side of the pale's wall. In the present invention, the fixing means therefore draws flatter and stresses only the part of the fence that requires stressing, and the fixing means can be kept hidden and protected by this stressed part when the pale is viewed from the front of the fence, since the fixing means need not penetrate the exterior convex side of the pale to fix it to the rail.


If one wanted to reduce the amount of material used in PHILLIPS's post, one would reduce the thickness of the concavo-convex shape, not make it hollow. Where one starts with a solid circular or semicircular section post, it is more natural to form that shape into a hollow form, as in CH 482087 (NOVOPLAST). Further, the fixing means in NOVOPLAST extends through both the front and the back of the post, exposing the fixing means to one viewing both the front and the back of the post, exposing the fixing means to one viewing the front of NOVOPLAST's post. Any teaching from NOVOPLAST would not therefore suggest that PHILLIPS was adapted to a hollow form, or that the fixing means should

engage the exteriorly concave side of the pale to draw it flatter and stress it."

Claims 11-18 are thus deemed to be allowable together with claim 19 which corresponds to claim 8 written in independent form and thus all of the claims in the case are deemed to be allowable.

5. A petition for an automatic one month extension of the term is enclosed together with a charge form applying the fee to a charge card of the undersigned.

Respectfully submitted,
The Firm of Karl F. Ross P.C.



By: Herbert Dubno, Reg. No. 19,752
Attorney for Applicant

ef-

14 August 2003
5676 Riverdale Avenue Box 900
Bronx, NY 10471-0900
Cust. No.: 535
Tel: (718) 884-6600
Fax: (718) 601-1099

Enclosures: Substitute Specification
Marked-up original specification
Petition for one month extension
Charge form for \$110.

Fencing System

This application is a national stage of PCT/GB00/03464 filed 8 September 2000 and is based upon the U.K. national application, UK 24 212 045 of 9 September 1999 under the International Convention.

SPECIFICATION CROSS REFERENCE TO RELATED APPLICATIONS

The present invention relates to a fencing system, in particular, but not exclusively, to palisade fencing.

5

BACKGROUND OF THE INVENTION

In a known type of palisade fencing, vertical pales are attached to a number of horizontal rails. These in turn are attached to vertical posts, which are set in the ground. The pales are usually bolted or riveted to the horizontal rails.

10

A pale is conventionally a strip of material such as metal of generally curved cross section, and is mounted upon the horizontal rails by its concave surface, so as to present its convex surface. When using such a palisade for an enclosed boundary, these convex surfaces are usually facing

15 outwards. A known pale has a cross section of a flattened trefoil shape. Such a pale is usually formed by cold rolling a strip of metal.

20

Holes through the thickness of the pale are formed, each hole corresponding to a hole in the horizontal rail to which the pale is to be attached. A bolt is then used to fasten the pale and the horizontal rail, the head of the bolt being upon the convex surface of the pale. Similar attachment means such as rivets or the like, may be substituted.

25

This bolt head is very apparent, and offers an enticing target for vandals. Should the bolt head be removed, by being sheared off with a cold chisel for example, the pales may be removed and access gained to the area enclosed by the palisade. Also, while a pale with a generally curved cross section has good structural strength axially, it has poor strength perpendicular to the axis.

GB 2 241 721 (Murphy et al) discloses a method of joining the pales to the horizontal rails without using bolts, rivets or the like. The pale, having a cross section of a flattened trefoil shape, also features a lip along each vertical edge. A clamping plate engages with these lips, and this is then bolted or riveted to the horizontal rail. In this manner the fastening means is concealed from someone on the outside of the boundary. Similarly to a conventional pale, this pale is cold rolled.

10 Like a conventional pale, the pale disclosed in Murphy has poor strength perpendicular to its axis. Also the lips may deform if the pale is pulled upon, so allowing the pale to be detached from the horizontal rails.

OBJECT OF THE INVENTION

The object of the present invention is to provide a system of fencing which is both structurally strong, and conceals its means of attaching the component parts when regarded from one side of the fencing.

SUMMARY OF THE INVENTION

According to the invention there is provided a fencing system including a plurality of pales, one or more substantially horizontal rails, the rails including a substantially flat surface against which the pales are set, wherein the pales include a tubular cross section comprising a tubular wall a part of which is provided with holes through which a bolt or the like may pass to secure the pales.

25 Preferably the cross section of the pale has a shape which is elongate in the direction of the rail

Each pale may have a substantially hollow section which includes a generally concave surface, the securement means engaging with this surface

and being concealed by this surface when the pale is regarded from side of the pale opposite to the concave surface.

5 Preferably the concave surface of the pale and surface of the rail (or an intermediate member situated between the rail and the pale) which it faces are, at least before securement, of different shapes so that a portion of the concave surface is not directly in contact with the rail, and the securement means pull upon this portion of the concave surface of the pale such that it becomes prestressed

10

Preferably the securement means include a bolt passing through both the rail and the concave surface. Preferably the generally concave surface includes a flat central portion. The pale is preferably formed ^{by} cold rolling or welded round tube into the desired cross section. The pale can formed directly from strip by forming the strip into a tube and then welding it and then forming the tube into desired cross section. Alternatively the pale can be cold formed from pre-made tube. The pale may also be conveniently made by extrusion.

15

20 According to another aspect of the present invention, there is provided a pale as herein defined.

25

The pale, when viewed in cross section, has a rear wall comprising a curved surface which is arranged against the horizontal rails and attached thereto, this rear wall forming part of the hollow section. When the fence is approached from the front, the concavity of the rear wall will shield the securement means.

Furthermore, a securement means, such as a bolt, common to both the rail and the pale and which tends to pull the curved surface of the pale towards the rail, will tend to flatten the concavity and prestress the pale, making the pale more rigid against the rail and making it very difficult to gain access to the securement means through the regions where the rail and pale abut.

BRIEF DESCRIPTION OF THE

A fencing system embodying the invention will now be described, by way of example, with reference to the drawings, of which;

10 *the sole figure,*
Figure 1 ⁱⁿ shows a sectional view of the pale and the horizontal rail at the attachment point.

SPECIFIC DESCRIPTION

Referring to Figure 1, the pale 20 has a generally crescent shaped hollow cross section, including a curved front wall 22, and a curved back wall 23. Rather than cusps, the regions 25,26 where the front and back walls meet are rounded. The pale then has a concave surface (the back wall 23), and a convex surface (the front wall 22).

20 The back wall 23 is placed against the rail 10, so that the rounded portions 25,26 rest directly against the rail. Each pale has a hole 28 centrally located in the concave surface, and the rail has corresponding holes 29 along its length. To secure the pale to the rail, the two holes 28,29 are aligned and a bolt 15 introduced to them. The generally concave
25 surface of the back wall is substantially flat at the central region where the hole ^{is provided} occurs. This makes it easier to form the hole 28 in the pale, and easier to introduce the bolt to the hole 28.

The hole 28 in the pale is such a size that the thread of the bolt 15 engages with it, whilst the hole 29 of the rail is somewhat larger, the bolt being constrained against the rail by its head. The hole 28 is a threaded hole and in order to provide sufficient engagement with the thread of the bolt, the corresponding female thread will have to extend to a greater extent than the thickness of the wall of the pale. This additional female thread can be provided by thickening of the wall at that point, or by providing a separate nut means ^{on} to the pale at the hole. Conveniently this may be provided by a threaded pot rivet which is introduced into the hole when the pale is connected to the rail from the rail side and expands to form a threaded part on the pale side of the hole 28. Alternatively a flow drilling may be used which creates an extended threaded portion from the existing hole which could be achieved by means of a self tapping bolt means.

As the bolt is tightened, the back wall 23 is drawn by the bolt's thread towards the rail 10. The crescent shape of the pale is drawn somewhat flatter as the pale is stressed.

When the pale is attached to the rail in this prestressed state, the securing bolt 15 is covered by the overhanging portions of the pale 20 when considered facing the front convex wall of the pale. In order to remove the pale from this side of the fencing, an intruder would have to force a tool or lever between one of the rounded portions 25,26 and the rail. This is difficult, since a large force is needed to overcome the prestressing of the pale.

When conventional pales are removed, the intruder will sometimes conceal that fact by resting the removed pales loosely against the pale, or temporarily fixing the pales, with chewing gum for example. To a casual

observer, the pales look undamaged, but the intruder may conveniently remove the pales to gain access to the fenced off region on subsequent occasions.

5 The pale illustrated in figure 1 includes indentations 31,32 which run the length of the pale. When a large predetermined force is applied between pale and the rail, the pale collapses and buckles. This occurs before the bolt fails. This buckling makes it obvious from a distance that the pale has been tampered with and needs replacing. Means for testing for
10 failed bolts or rivets have been devised such as passing along the fence with a stick rapping against the pales and detecting the change in the sound which would indicate a faulty bolt or rivet. Such labor~~y~~ intensive testing methods are no longer required with the fencing system of this invention.

15 The particular shape of the cross section of the pale and in particular the indentations 32 are important in determining the mode of failure of the pale which determines nature of the collapse and makes it possible for the pale to be observed as having failed.

20 The hollow section of the pale provides great strength and rigidity perpendicular to the pale's axis, whil~~st~~^e losing none of the axial strength.

The horizontal rails may then be attached to vertical posts embedded in the ground in the conventional manner.

25 The pale is formed by forming a strip first into a round tubular cross section and welding it and subsequently forming the welded tube into the desired cross section if required, though other methods could be employed. For example, the pale may be~~is~~ formed by rolling a shape having a similar

cross section but with an open shape instead of the hollow section, and then
^{done} bent and welding the shape to form the tubular section.

5 The pale may also be formed by extruding metal through an aperture of the required shape to produce the required cross section. Other materials, such as composite materials, could equally well be used.

10 At the top of the pale, the front wall could be axially subdivided and the resulting strips flared out to form an upper projection, known as a topping, in a similar way to conventional pales. Alternatively, the hollow section could be left open, and a topping fitted into the open top of the pale.

The horizontal rail 10 illustrated here is a standard strip, though rails having other cross sections could be used with equal facility.

15

Equally, the rail illustrated has a uniform, flat surface facing the concave surface of the pale. The rail surface could though take a variety of shapes. It could be a convex surface with a curvature less than that of the concave surface of the pale. It could also be a convex shape corresponding
20 to the concavity of the pale, and although no prestressing will occur, the bolt will be concealed by the pale.

25 The concealing portion of the pale need not be smoothly curved, but may be a re-entrant shape composed of flat surfaces and sharp angles, even to the extent of being rectangular. Naturally, the pale need not abut directly against the rail, but an intermediate member could be inserted between the rail and the pale.